



## Green Pin® Omega Link S/S-GR5

### Grade 5 stainless steel omega link



COI


- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1

for chain diameter		working load limit	width	diameter pin	width	length inside	width bow	length outside	thickness	width outside	width outside	thickness	weight each
mm	inch		a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
5	<sup>3</sup> / <sub>16</sub>	0.5	14	6	7	26	20	53	13	41	28	6	0.07
6	<sup>7</sup> / <sub>32</sub>	0.7	14	8	7	25	20	53	13	41	28	6	0.07
7 - 8	<sup>1</sup> / <sub>4</sub> - <sup>5</sup> / <sub>16</sub>	1.2	20	9	9	34	24	71	16	55	32	8	0.18
10	<sup>3</sup> / <sub>8</sub>	1.6	19	13	12	40	31	82	17	63	42	11	0.28
13	<sup>1</sup> / <sub>2</sub>	2.7	25	16	15	51	40	106	20	84	54	14	0.64



## Green Pin® Connecting Link S/S-GR5

### Grade 5 stainless steel connecting link



MJI

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1

for chain diameter		working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	weight each
mm	inch		a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
6	<sup>7</sup> / <sub>32</sub>	0.7	8	42	11	20	52	11	15	0.09
7 - 8	<sup>1</sup> / <sub>4</sub> - <sup>5</sup> / <sub>16</sub>	1.2	9	53	14	20	55	13	19	0.16
10	<sup>3</sup> / <sub>8</sub>	1.6	10	66	18	23	64	18	23	0.28
13	<sup>1</sup> / <sub>2</sub>	2.7	14	83	21	32	85	24	28	0.64

INFO