



Green Pin® Sling Hook E S/S-GR5

Grade 5 stainless steel eye sling hook

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®]



CSCI


for chain diameter		working load limit	length	diameter		width opening	thickness	width	diameter		length	width	thickness	weight each
mm	inch			inside eye	mm				eye outside	mm				
mm	inch	t	a	b	c	d	e	f	g	h	i	j	kg	
6	7/32	0.7	84	23	26	15	20	43	72	114	10	6	0.28	
7 - 8	1/4 - 5/16	1.2	103	26	30	20	24	51	87	139	12	8	0.56	
10	3/8	1.6	128	35	33	24	29	65	106	172	15	10	1.09	
13	1/2	2.7	152	41	37	32	39	77	133	209	18	12	1.98	



Green Pin® Sling Hook CL S/S-GR5

Grade 5 stainless steel clevis sling hook

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®]



CSCI

for chain diameter		working load limit	length	width		width opening	thickness	width	width outside		length	diameter pin	weight each
mm	inch			a	b				c	d			
mm	inch	t	a	b	c	d	e	f	g	h	i	kg	
5	3/16	0.5	76	7	26	15	20	28	72	108	6	0.29	
6	7/32	0.7	75	7	26	15	20	28	72	108	8	0.29	
7 - 8	1/4 - 5/16	1.2	95	9	30	20	24	32	87	136	9	0.58	
10	3/8	1.6	113	12	33	24	29	42	106	164	13	1.1	
13	1/2	2.7	138	15	37	32	39	54	133	208	16	1.86	