



## Green Pin BigMouth® Dee Shackle BN

Dee shackle with a longer inside length, wider mouth and safety bolt

- **Material:** bow and pin alloy steel, grade 8, quenched and tempered
- **Safety Factor:** MBL equals 5 x WLL
- **Standard:** ASME B30.26
- **Finish:** hot dipped galvanized
- **Temperature Range:** -20°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MTC<sup>a</sup> CE



G-4553

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	thickness nut	weight each
t	a	b	c	d	e	f	g	h	i	kg
4.6	19	22	46	19	70	116	169	154	19	1.50
8.6	25	28	59	25	83	140	208	190	25	3.15
15.5	38	42	88	38	115	178	281	257	19	9.50

In inch

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	thickness nut	weight each
t	inch	inch	inch	inch	inch	inch	inch	inch	inch	lbs
4.6	$\frac{3}{4}$	$\frac{7}{8}$	$1 \frac{13}{16}$	$\frac{3}{4}$	$2 \frac{3}{4}$	$4 \frac{9}{16}$	$6 \frac{21}{32}$	$6 \frac{1}{16}$	$\frac{3}{4}$	3.30
8.6	1	$1 \frac{1}{8}$	$1 \frac{5}{16}$	1	$3 \frac{1}{4}$	$5 \frac{1}{2}$	$8 \frac{3}{16}$	$7 \frac{15}{32}$	1	6.90
15.5	$1 \frac{1}{2}$	$1 \frac{5}{8}$	$1 \frac{15}{32}$	$1 \frac{1}{2}$	$4 \frac{9}{16}$	7	$11 \frac{1}{16}$	$10 \frac{1}{8}$	$\frac{3}{4}$	20.94