# Green Pin® Wire Rope Clip

## Wire rope clip generally to EN 13411-5 Type B

- **Material:** bridge: drop forged high tensile steel SAE 1045
  U-bolt: SAE 1015
- **Standard:** EN 13411-5 Type B
  formerly U.S. Federal Specification FF-C-450D
- **Finish:** hot dipped galvanized
  U-bolt and/or nuts for diameter bow 5, 6, 8 and 10 are electro galvanized
- **Certification:** 2.1

| diameter wire rope | diameter | length bow | width inside | length thread | length base | thickness base | height base | weight per 100 pcs |
|---|---|---|---|---|---|---|---|---|
| | a | b | c | d | e | f | g | |
| mm | mm | mm | mm | mm | mm | mm | mm | kg |
| 3 - 4 | 5 | 24 | 12 | 11 | 24 | 21 | 10 | 2 |
| 5 | 6 | 31 | 15 | 13 | 29 | 24 | 13 | 4 |
| 6 - 7 | 8 | 34 | 19 | 13 | 37 | 30 | 18 | 8 |
| 8 | 10 | 45 | 22 | 19 | 43 | 33 | 19 | 14 |
| 9 - 10 | 11 | 49 | 26 | 19 | 49 | 42 | 25 | 19 |
| 11 | 12 | 60 | 30 | 25 | 58 | 46 | 26 | 31 |
| 12 - 13 | 13 | 61 | 30 | 25 | 58 | 48 | 31 | 34 |
| 14 - 15 | 14 | 72 | 33 | 32 | 63 | 52 | 31 | 36 |
| 16 | 14 | 74 | 33 | 32 | 64 | 54 | 36 | 45 |
| 18 - 20 | 16 | 86 | 38 | 37 | 72 | 57 | 38 | 68 |
| 22 | 19 | 98 | 45 | 41 | 80 | 62 | 40 | 108 |
| 24 - 26 | 19 | 108 | 48 | 46 | 88 | 67 | 47 | 113 |
| 28 - 30 | 19 | 117 | 51 | 51 | 91 | 73 | 48 | 140 |
| 32 - 34 | 22 | 130 | 59 | 54 | 105 | 79 | 56 | 207 |
| 36 | 22 | 140 | 60 | 59 | 108 | 79 | 58 | 234 |
| 38 - 40 | 22 | 147 | 66 | 60 | 112 | 85 | 64 | 266 |
| 41 - 42 | 25 | 161 | 70 | 67 | 121 | 92 | 67 | 329 |
| 44 - 46 | 29 | 174 | 78 | 70 | 134 | 97 | 76 | 441 |
| 48 - 52 | 32 | 195 | 86 | 78 | 150 | 113 | 85 | 603 |
| 56 - 58 | 32 | 213 | 98 | 81 | 162 | 116 | 100 | 707 |
| 62 - 65 | 32 | 227 | 105 | 87 | 168 | 119 | 113 | 806 |
| 68 - 72 | 32 | 243 | 112 | 91 | 174 | 127 | 124 | 1000 |
| 75 - 78 | 38 | 271 | 121 | 98 | 194 | 135 | 136 | 1440 |

In inch

| diameter wire rope | diameter | length bow | width inside | length thread | length base | thickness base | height base | weight per 100 pcs |
|---|---|---|---|---|---|---|---|---|
| | a | b | c | d | e | f | g | |
| inch | inch | inch | inch | inch | inch | inch | inch | lbs |
| 1/8 | 3/16 | 15/16 | 15/32 | 7/16 | 15/16 | 13/16 | 13/32 | 4.4 |
| 3/16 | 1/4 | 1 7/32 | 19/32 | 1/2 | 1 5/32 | 15/16 | 1/2 | 8.8 |
| 1/4 | 5/16 | 1 11/32 | 3/4 | 1/2 | 1 15/32 | 1 3/16 | 23/32 | 17.6 |
| 5/16 | 13/32 | 1 25/32 | 7/8 | 3/4 | 1 11/16 | 1 5/16 | 3/4 | 28.7 |
| 3/8 | 7/16 | 1 15/16 | 1 1/32 | 3/4 | 1 15/16 | 1 21/[illegible] | 31/32 | 42 |
| 7/16 | 15/32 | 2 3/8 | 1 3/16 | 31/32 | 2 9/32 | 1 13/16 | 1 1/32 | 73 |
| 1/2 | 1/2 | 2 13/32 | 1 3/16 | 31/32 | 2 9/32 | 1 7/8 | 1 7/32 | 75 |
| 9/16 | 9/16 | 2 27/32 | 1 5/16 | 1 1/4 | 2 15/32 | 2 1/16 | 1 7/32 | 99 |
| 5/8 | 9/16 | 2 29/32 | 1 5/16 | 1 1/4 | 2 17/32 | 2 1/8 | 1 13/32 | 99 |
| 3/4 | 5/8 | 3 3/8 | 1 1/2 | 1 15/32 | 2 27/32 | 2 1/4 | 1 1/2 | 150 |
| 7/8 | 3/4 | 3 27/32 | 1 25/32 | 1 5/8 | 3 5/32 | 2 7/16 | 1 9/16 | 238 |
| 1 | 3/4 | 4 1/4 | 1 7/8 | 1 13/16 | 3 15/32 | 2 5/8 | 1 7/8 | 249 |
| 1 1/8 | 3/4 | 4 19/32 | 2 | 2 | 3 19/32 | 2 7/8 | 1 7/8 | 309 |
| 1 1/4 | 7/8 | 5 1/8 | 2 5/16 | 2 1/8 | 4 1/8 | 3 1/8 | 2 7/32 | 456 |
| 1 3/8 | 7/8 | 5 1/2 | 2 3/ | | | | | |