



Green Pin® Master Link Assembly S/S-GR5

Grade 5 stainless steel master link assembly


- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MTC^b



MTSI

diameter	diameter chain 2 legs		working load limit	length inside	width inside	diameter	length inside	width inside	thickness	weight each
a mm	$\beta \leq 45^\circ$ mm	$\beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	e mm	f mm	g mm	kg
18	6	6	1.6	135	75	13	54	25	6	1.17
22	8	8	2.65	160	90	16	70	34	8	2.17
26	10	10	4.25	180	100	18	85	40	8	3.34
32	13	13	6.7	200	110	22	115	50	13	5.99

In inch



diameter	diameter chain 2 legs		working load limit	length inside	width inside	diameter	length inside	width inside	thickness	weight each
a inch	$\beta \leq 45^\circ$ inch	$\beta \leq 60^\circ$ inch	t	b inch	c inch	d inch	e inch	f inch	g inch	lbs
$\frac{23}{32}$	$\frac{7}{32}$	$\frac{7}{32}$	1.6	$5 \frac{5}{16}$	$2 \frac{15}{16}$	$\frac{1}{2}$	$2 \frac{1}{8}$	$\frac{31}{32}$	$\frac{1}{4}$	2.58
$\frac{7}{8}$	$\frac{5}{16}$	$\frac{5}{16}$	2.65	$6 \frac{5}{16}$	$3 \frac{17}{32}$	$\frac{5}{8}$	$2 \frac{3}{4}$	$1 \frac{11}{32}$	$\frac{5}{16}$	4.78
$1 \frac{1}{32}$	$\frac{3}{8}$	$\frac{3}{8}$	4.25	$7 \frac{3}{32}$	$3 \frac{15}{16}$	$\frac{23}{32}$	$3 \frac{11}{32}$	$1 \frac{9}{16}$	$\frac{5}{16}$	7.36
$1 \frac{1}{4}$	$\frac{1}{2}$	$\frac{1}{2}$	6.7	$7 \frac{7}{8}$	$4 \frac{11}{32}$	$\frac{7}{8}$	$4 \frac{17}{32}$	$1 \frac{31}{32}$	$\frac{1}{2}$	13.2

