


C

S-Hook

- **Material:** high tensile steel
- **Safety factor:** MBL equals 4 x LC
- **Finish:** painted red
- **Certification:** 2.1 2.2



S



lashing capacity	diameter	length	width	weight each
t	a mm	b mm	c mm	kg
0.2	10	80	30	0.11
0.3	13	100	40	0.24
0.5	16	130	50	0.47
0.75	18	170	60	0.8
1	20	185	64	1.02
1.2	22	200	69	1.4
1.5	24	230	80	1.95
2	32	270	90	3.5
3	36	325	98	5.16
4	40	350	112	7.48
5	45	400	130	10.81
6	51	450	150	16.2


C

S Eye Hook

- **Material:** high tensile steel
- **Safety factor:** MBL equals 4 x LC
- **Finish:** painted red
- **Certification:** 2.1 2.2



SO



lashing capacity	diameter	length	width	width inside	weight each
t	a mm	b mm	c mm	d mm	kg
0.2	10	80	30	16	0.11
0.3	13	100	40	21	0.25
0.5	16	130	50	25	0.48
0.75	18	160	59	34	0.76
1	20	180	65	42	1.07
1.2	22	195	69	37	1.4
1.5	24	220	79	40	1.79
2	32	260	90	46	3.8
3	36	320	99	52	5.35
4	40	360	115	59	7.85
5	45	390	126	68	10.95
6	51	450	150	77	15.2