




Green Pin® Self Locking Hook E GR10

Grade 10 eye self locking hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^b DGUV



UXLO



for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	7/32	1.4	111	24	32	16	26	47	77	147	11	7	0.51
8	9/32 - 5/16	2.6	134	29	43	23	29	57	92	176	14	7	0.91
10	3/8	4	168	35	47	32	35	69	111	219	17	10	1.79
13	1/2	6.8	199	46	61	37	45	87	142	264	20	13	3.36
16	5/8	10.3	247	59	74	43	56	111	185	328	26	16	7
20	3/4	16	283	70	90	52	61	126	205	372	28	20	9.22




Green Pin® Self Locking Hook CL GR10

Grade 10 clevis self locking hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^b DGUV



UXLC



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	7/32	1.4	92	7	32	16	26	28	77	131	8	0.49
	9/32	1.95	116	9	43	23	29	32	92	161	10	0.91
8	5/16	2.6	116	9	43	23	29	32	92	161	10	0.91
10	3/8	4	143	12	47	32	35	42	111	200	13	1.77
13	1/2	6.8	167	15	61	37	45	54	142	242	16	3.33
16	5/8	10.3	201	19	74	43	54	68	185	293	20	6.75
20	3/4	16	234	23	90	52	61	82	205	339	24	9.57