




Green Pin® Self Locking Hook S GR10

Grade 10 self locking hook with swivel

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] DGUV
- **Note:** equipped with needle roller thrust bearing to enable rotation under load



UXLE



for chain diameter		working load limit	length	length inside	width inside	width opening	thickness	width	width outside	length	diameter	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	$\frac{7}{32}$	1.4	122	32	32	32	16	26	77	192	12	6	0.78
8	$\frac{9}{32} - \frac{5}{16}$	2.6	148	39	37	43	23	29	92	231	14	8	1.39
10	$\frac{3}{8}$	4	183	46	48	47	32	35	111	282	16	11	2.56
13	$\frac{1}{2}$	6.8	214	57	58	61	37	45	142	336	21	14	4.56
16	$\frac{5}{8}$	10.3	269	65	73	74	39	56	185	416	24	17	9.37
20	$\frac{3}{4}$	16	304	87	82	90	52	61	205	476	24	21	12.7