




Green Pin® Self Locking Hook SCL EN 1677-3 GR8

Grade 8 swivel clevis self locking hook EN 1677-3



XLBA



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN 1677-3
- **Finish:** painted red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] DGUV
- **Note:** equipped with needle roller thrust bearing to enable rotation under load

for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
5	³ / ₁₆	0.8	148	7	32	17	27	56	77	188	6	0.7
6	⁷ / ₃₂	1.12	148	7	32	17	27	56	77	188	8	0.8
7 - 8	¹ / ₄ - ⁵ / ₁₆	2	176	9	43	24	31	65	92	221	9	1.4
10	³ / ₈	3.2	214	12	47	32	37	79	111	271	13	2.6
13	¹ / ₂	5.4	250	15	61	37	47	96	142	325	16	4.7
16	⁵ / ₈	8.2	319	19	74	43	67	121	185	411	20	9.8