



## Green Pin® Self Locking Hook E EN 1677-3 GR8

### Grade 8 eye self locking hook EN 1677-3



XLO

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-3
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup> DGUV
- **Note:** from 12.8 t without flat part

for chain diameter		working load limit	length	diameter inside eye		width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	inch			a mm	b mm									
5 - 6	<sup>3</sup> / <sub>16</sub> - <sup>7</sup> / <sub>32</sub>	1.12	111	24	32	16	26	47	77	147	11	7	0.51	
7 - 8	<sup>1</sup> / <sub>4</sub> - <sup>5</sup> / <sub>16</sub>	2	134	29	43	23	29	57	92	176	14	7	0.91	
10	<sup>3</sup> / <sub>8</sub>	3.2	168	35	47	32	35	69	111	219	17	10	1.79	
13	<sup>1</sup> / <sub>2</sub>	5.4	199	46	61	37	45	87	142	264	20	13	3.36	
16	<sup>5</sup> / <sub>8</sub>	8.2	247	59	74	43	56	111	185	328	26	16	7	
18 - 20	<sup>3</sup> / <sub>4</sub>	12.8	282	69	88	51	63	126	207	374	28	20	9.22	



## Green Pin® Self Locking Hook EN 1677-3 CL GR8

### Grade 8 clevis self locking hook EN 1677-3



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-3
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup> DGUV

for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch											
5	<sup>3</sup> / <sub>16</sub>	0.8	92	7	32	16	26	28	77	131	6	0.49
6	<sup>7</sup> / <sub>32</sub>	1.12	92	7	32	16	26	28	77	131	8	0.49
7-8	<sup>1</sup> / <sub>4</sub> - <sup>5</sup> / <sub>16</sub>	2	116	9	43	23	29	32	92	161	9	0.91
10	<sup>3</sup> / <sub>8</sub>	3.2	143	12	47	32	35	42	111	200	13	1.77
13	<sup>1</sup> / <sub>2</sub>	5.4	167	15	61	37	45	54	142	242	16	3.33
16	<sup>5</sup> / <sub>8</sub>	8.2	201	19	74	43	56	68	185	293	20	6.75
18 - 20	<sup>3</sup> / <sub>4</sub>	12.8	232	23	88	51	63	82	207	341	24	9.57

XLC.55 -8.647 -0100.59-8.6479.845 .59-8.6471-0.3979-0.1437 48 -10211437 48 -13.41437 48 l-13.41437 48 l-4-Q5544 7 48 40.6471-0.3